



## SHALLOW WELL JET PUMPS



**MODEL 3110P 1 HP**  
**MODEL 3107P 3/4 HP**  
**MODEL 3105P 1/2 HP**

- Superior performance to depths of water 25' or less
- Fiberglass reinforced thermoplastic pump housing for the highest corrosion resistance
- Energy efficient motor
- 3/4 and 1 HP ready to install heavy-duty dual voltage motor pre-set at 230 volts
- 1/2 HP ready to install heavy-duty dual-voltage motor preset at 115 volts
- Self priming after pump housing is initially filled protects against overheating
- 1-1/4" NPT suction and 1" NPT discharge pipe size



### PERFORMANCE

Model	HP	Warranty	Voltage	Amps	Pressure Switch		GPM Pumped at Different Depths to Water*					Pressure Shut-off
					On	Off	5'	10'	15'	20'	25'	
3110P	1	1-year	115/230	14.8/7.4	30	50	16.4	16.1	14.1	12.0	8.1	67 PSI
3107P	3/4	1-year	115/230	12.2/6.1	30	50	10.3	9.7	8.2	7.1	5.1	78 PSI
3105P	1/2	1-year	115/230	9.4/4.7	30	50	7.4	6.4	6.1	5.0	4.0	77 PSI

\*All performances shown in gallons per minute at 40 PSI (pound per square inch) discharge pressure at top of well.

### ORDERING INFORMATION

Model	UPC	Carton (L x W x H)	Cube	Pallet Qty.	Weight
3110P	0 22315 31512 9	22.813" x 11.063" x 10.5"	1.534	24	26 lbs.
3107P	0 22315 31511 2	22.813" x 11.063" x 10.5"	1.534	24	24 lbs.
3105P	0 22315 31510 5	22.813" x 11.063" x 10.5"	1.534	24	21 lbs.